

UH-2000 handheld transmitter

Features



- Multi-function LCD display for channel/frequency, sensitivity, battery status indicator, Alkaline/NiMH battery selection.
- 1000 frequencies agile in 25 MHz bandwidth.
- ± 40 KHz peak deviation.
- 35 mW maximum transmission power.
- Rotatable protective cap hides the function keys (POWER, UP, DOWN, SET) for fool proof operation.
- Power-ON LED.
- Uses 2 pcs AA batteries to operate.
- Low current consumption.
- Long operating time up to 12 hours.
- Hidden antenna.
- Detachable microphone capsule design.
- Dynamic and condenser microphone capsules available.
- Rubberized coating.
- Multi-color cap for channel identification.
- FCC and CE approved.
- Matching battery charger: HC-30

Specifications

Model	UH-2000
Frequency Range	UHF High Band 600 - 900 MHz
Switching Bandwidth	25 MHz
Switchable Frequency	1000
RF Power Output	< 35mW**
Spurious Emission	> 60 dB below carrier
Dynamic Range	> 110 dB
Display Screen	LCD
T.H.D	< 0.5%
Peak Deviation	± 40 KHz
Antenna	Built-in
Battery Type	AA x 2
Operating Life (Alkaline)	about 12 hours (Alkaline)
Charging Function	YES
Battery charger	HC-30
Microphone Capsule	Dynamic/ Condenser type
Dimension (mm)	$\phi 46 \times 240$
Weight (g)	200
Approval	CE,FCC

** Remark: The above specifications are subject to change without prior notice. The output power may vary from country to country.